Steel Wire Basket Tray



Brackets

Tablok™ Profile

- · Reduces installation time
- Locks tray into position no hardware required



Cat. No.	Number of tabs per length	Length (L)		Weight	
		in.	mm	lb./ea.	kg/ea.
ETB-TL-06-PG	2	6	150	0.48	0.19
ETB-TL-08-PG	2	8	200	0.59	0.27
ETB-TL-10-PG	2	10	250	0.73	0.33
ETB-TL-12-PG	2	12	300	0.88	0.40
ETB-TL-16-PG	2	16	400	1.17	0.53
ETB-TL-20-PG	2	20	500	1.47	0.67
ETB-TL-24-PG	2	24	600	1.76	0.80
ETB-TL-28-PG	2	28	700	2.05	0.93
ETB-TL-120-PG*	14	120	3048	8.78	3.99

For trapeze hung installations, specify TabLok $^{\!\scriptscriptstyle{\text{TM}}}$ profile 4 in. longer than width tray.

Example:

For ETU2012SE10 (12 in. wide) use ETB-TL16-PG (16 in. wide)

Drastically reduce installation time with the TabLokTM profile. Used to mount tray on walls, floors and cabinets, the TabLokTM profile locks the basket tray into position eliminating the need for any additional hardware.

Compatible with all ExpressTray® tray, the TabLok™ profile has a pregalvanized steel finish and is available in 9 lengths for use with tray widths ranging from 2 in. to 24 in. wide. For field cuts, a 120 in. (3048 mm) length is also available.

The TabLok^T profile can also be used for trapeze hung and center hung installations.

EXPRESS

Refer to pages C45, C46, C48 and C49 for application examples.

____c

Tool required: screwdriver





^{*} Not pictured here