


## Accessories

### Bracket Clamp



### Dimensions



The bracket clamp is used for mounting tray to wall brackets or suspended support brackets and is compatible with all tray profiles. Available in electro-galvanized steel, pregalvanized steel, hot-dipped galvanized steel and stainless steel (304 or 316).

**EXPRESS TIP**

Refer to pages C48, C49 and C51 for application examples.



Tool required: 10mm nut driver

Cat. No.	Material	Weight	
		lb./ea.	kg/ea.
ETH-WBC-EG	Electro-galvanized Steel	0.09	0.02
ETH-WBC-HD	Hot-dipped galvanized Steel		
ETH-WBC-SS	Stainless Steel (Type 304)		
ETH-WBC-S6	Stainless Steel (Type 316)		

### Standard Bolting Kit



The standard bolting kit consists of an M6 x 12mm carriage bolt and capture nut. Available in electro-galvanized steel, hot-dipped galvanized steel and stainless steel (304 and 316).



Tool required: 10mm nut driver

Cat. No.	Material	Weight	
		lb./ea.	kg/ea.
ETH-KIT0-EG	Electro-galvanized Steel	0.02	0.01
ETH-KIT0-HD	Hot-dipped galvanized Steel		
ETH-KIT0-SS	Stainless Steel (Type 304)		
ETH-KIT0-S6	Stainless Steel (Type 316)		