

## Accessories

### Nested “J” or “L” Bracket Bolting Kit

For use with “J” and “L” brackets, this bracket bolting kit consists of an M10 x 25mm carriage bolt and capture nut. Available in hot-dipped galvanized steel.



**EXPRESS TIP**

Refer to page C49 for an application example.



Tool required: 17mm nut driver

Cat. No.	Material	Weight	
		lb./ea.	kg/ea.
<b>ETH-KIT1-HD</b>	Hot-dipped galvanized Steel	0.09	0.04

### Back-to-Back Bracket Bolting Kit



For use in back-to-back bracket configurations or for use with “L” brackets, this bracket bolting kit consists of an hexagonal M10 x 60mm bolt, a flat washer, a lock washer and a nut. Available in hot-dipped galvanized steel.

**EXPRESS TIP**

Refer to page C49 for an application example.



Tool required: 17mm nut driver

Cat. No.	Material	Weight	
		lb./ea.	kg/ea.
<b>ETH-KIT2-HD</b>	Hot-dipped galvanized Steel	0.13	0.06

### Spacers



The spacer is used to prevent spreading of the bracket profile during installation. Spacers can be used with both “L” and “J” brackets in both single and back-to-back configurations. Available in pregalvanized and hot-dipped galvanized steel.

**EXPRESS TIP**

Refer to pages C48 and C49 for application examples.

Cat. No.	Material	Weight	
		lb./ea.	kg/ea.
<b>ETH-S-PG</b>	Pregalvanized Steel	0.09	0.04
<b>ETH-S-HD</b>	Hot-dipped galvanized Steel		