

## Couplings

### Sleeve Coupling (for repair work)



No internal stop

Part No.	Size	Std. Ctn. Qty.
E200J	2"	30
E200L	3"	25
E200M	3 1/2"	20
E200N	4"	15
E200P	5"	8
E200R	6"	5

### Coupling



Part No.	Size	Std. Ctn. Qty.
E940F	1"	50
E940H	1 1/2"	25
E940J	2"	30
E940K	2 1/2"	20
E240L	3"	30
E240N	4"	15
E240P	5"	20
E240RF	6"	5

### Long Line Coupling




Part No.	Size	Std. Ctn. Qty.
E941H	1 1/2"	40
E941J	2"	25
E941K	2 1/2"	15
E241L	3"	15
E241N	4"	10

### 5° Angle Coupling BxS

(Bell x Spigot)



Part No.	Size	C	Std. Ctn. Qty.
E244J	2"	2.13	15
E244L	3"	3.25	5
E244NF	4"	3.50	15
E244NF5 (short)	4"	1.87	25
E244PF	5"	4.13	10
E244PF5 (short)	5"	2.00	20
E244RF	6"	5.13	5
E244RF5 (short)	6"	2.25	10



### 5° Angle Coupling BxB (Bell x Bell)



Part No.	Size	Std. Ctn. Qty.
E2440NF	4"	15
E2440PF	5"	10
E2440RF	6"	5

### 5° Angle Coupling BxB (Swedged)



Part No.	Size	Std. Ctn. Qty.
E245J	2"	20
E245N	4"	10
E245P	5"	10
E245R	6"	5

## Plugs

### Plug



Part No.	Size	Std. Ctn. Qty.
P258H	1 1/2"	50
P258K	2 1/2"	50

### Plug with Pull Tab



Part No.	Size	Std. Ctn. Qty.
P258JT	2"	60
P258LT	3"	30
P258NT	4"	48
P258PT	5"	30
P258RT	6"	30

## Swedge Coupling

Part No.	Size	Std. Ctn. Qty.
E242J	2"	48

### 5° Angle Coupling S x S

Part No.	Size	Std. Ctn. Qty.
E2440N5	4"	15
E2440P5	5"	20

## Expansion Fittings



E945 series expansion fittings are designed to compensate for length changes due to temperature variations in exposed conduit runs.

- EXCLUSIVE Molded in Mid-point indicator on the piston.
- EXCLUSIVE 2" Expansion Fitting with an 8" travel distance.
- Two-piece molded design with lubricated seals for easier movement for the life of the product.
- Ridges on the fitting for easier installation (Sizes 2" through 6" only).
- Male terminal Adapter End design (1/2" – 2" NPT Threads, and 2 1/2" – 6" NPSC Threads).
- Two O-Rings to prevent leakage.
- Can be installed vertically or horizontally.



Coupling End Part No.	Male Terminal Adapter End Part No.	Size	Std. Ctn. Qty.	Travel Length (in.)
E945D	E945DX	1/2	20	4"
E945E	E945EX	3/4	15	4"
E945F	E945FX	1	10	4"
E945G	E945GX	1 1/4	5	4"
E945H	E945HX	1 1/2	5	4"
E945J	E945JX	2	15	8"
E945K	E945KX	2 1/2	10	8"
E945L	E945LX	3	10	8"
E945M	E945MX	3 1/2	5	8"
E945N	E945NX	4	5	8"
E945P	E945PX	5	1	8"
E945R	E945RX	6	1	8"

## Couplings




### Standard Couplings

All socket fittings should be attached Using Carlon solvent cement.



Socket type for joining nonmetallic conduit.



Part No.	Size	Std. Ctn. Qty.	A Typical	B	I.D.	O.D.	C Typical	L
E940D	1/2	150	.852	.836	.728	1 7/64	1 1/16	1 1/2
☛ CE940DR-CTN	1/2	75	.852	.836	.728	1 7/64	1 1/16	1 1/2
E940E	3/4	100	1.064	1.046	.840	1 5/16	3/4	1 5/8
☛ CE940ER-CTN	3/4	45	1.064	1.046	.840	1 5/16	3/4	1 5/8
E940F	1	50	1.330	1.310	1.210	1 5/8	1 5/16	2
☛ CE940F-UPC	1	50	1.330	1.310	1.210	1 5/8	1 5/16	2
E940G	1 1/4	30	1.677	1.655	1.535	1 63/64	1	2 1/8
E940H	1 1/2	25	1.918	1.894	1.755	2 15/64	1 1/8	2 3/8
E940J	2	30	2.393	2.369	2.190	2 47/64	1 3/16	2 1/2
E940K	2 1/2	20	2.890	2.868	2.688	3 5/16	1 33/64	3 3/16
E940L	3	25	3.515	3.492	3.375	3 31/32	1 3/4	3 13/32
E940M	3 1/2	20	4.015	3.992	3.780	4 9/16	1 3/4	3 5/8
E940N	4	15	4.515	4.491	4.265	5 3/32	1 25/32	3 3/4
E940P	5	8	5.593	5.553	5.097	6 1/4	1 5/16	4 1/16
E940R	6	5	6.658	6.614	6.115	7 1/2	2 3/16	4 5/8

☛ Canada only

Schedule 40 & 80 Elbows & Fittings

## Short Expansion Couplings

(Expands to a maximum of 2")



Part No.	Size	Std. Ctn. Qty.
E955D	1/2	40
E955E	3/4	40
E955F	1	25
E955G	1 1/4	15
E955H	1 1/2	10
E955J	2	6

## Special Long Line Couplings



Long Line Couplings

Part No.	Size	Std. Ctn. Qty.	Std. Wt. (lbs.)	Length
E941H	1 1/2	40	9	3.19
E941J	2	25	8	3.59
E941K	2 1/2	15	8	4.29
E941L	3	15	14	6.44
E941N	4	10	15	6.96
E941PF	5	4	12	9.63
▶ E941RF	6	5	21	11.75

## Fabricated Expansion Couplings



Part No.	Size	Std. Ctn. Qty.	Travel Length (in.)
E945KXL	2 1/2	10	12