

## **Tools and Dies**

## Battpac® LT BPLT15BSCR 15-Ton Battery-Powered Compression Tool

- · Rotating head allows maximum flexibility for crimping
- Double-speed feature decreases crimp time by doubling jaw speed until it reaches load
- Includes two Makita 14.4V Ni-MH batteries (3.0 AMP Hrs.)
- Built-in LED battery power indicator
- On-tool DC power jack



#### ...... Specifications ......

Installing Range:

Up to 1500 kcmil copper lugs & splices

Up to 1000 kcmil aluminum lugs & splices

CHT814-10 to CHT750-350-1F copper H-taps

63105 to 63180 aluminum H-taps 54755 to 54790 C-taps

- Output Force: 15 tons
- Dimensions (L x W x H): 21" x 3½" x 11"
- Battery: 14.4V 3.0Ah Ni-MH
- Weight with Battery: 23.75 lbs.

CAT. NO.	DESCRIPTION	PKG. QTY.
BPLT15BSCR	Battpac® LT 15-Ton Compression Tool. Includes carrying case, charger, two batteries, and carry strap	1

## **TBM15I 15-Ton Hydraulic Crimping Head**

- · Head made of forged steel and insulated with rubber boot
- Longer, slimmer design enables easier access into tight spaces, such as in cable tray and central office applications
- · Wider jaw opening eases crimping of larger lugs, C-taps and H-taps
- Uses 15600 Series dies; can also use 15500 Series dies with 15500-TB adapter



#### ..... Specifications .....

- Installing Range:
  - Up to 1500 kcmil copper lugs & splices

Up to 1000 kcmil aluminum lugs & splices

CHT814-10 to CHT750-350-1F copper H-taps

63105 to 36180 aluminum H-taps 54755 to 54790 C-taps

- · Output Force: 15 tons
- Operating Pressure: 10,000 psi nominal
- Dimensions (L x W x H): 15¾" x 25½" x 4½"
- Weight without Dies: 16.5 lbs.

		PKG.		
CAT. NO.	DESCRIPTION	QTY.		
TBM15I	Insulated 15-Ton Hydraulic Head with Steel Case	1		
15600 Series — Fits directly into tool for larger size connectors, 800 kcmil-1500 kcmil				
15500 Series	— Used in conjunction with 15500-TB Adapter, #8 AWG-750 kcmil			

# 21940 40-Ton Hydraulic Crimping Head

- Compact design delivers maximum pressure for larger lugs and splices
- Ideal for applications requiring larger lugs up to 2000 kcmil
- Uses 11300 and 11400 Series dies



Creates hex-style crimp



Installing Range:

Up to 2000 kcmil copper lugs & splices

Up to 2000 kcmil aluminum lugs & splices

Output Force: 40 tons

#### ...... Specifications ......

- Operating Pressure: 10,000 psi nominal
- Dimensions (L x W x H): 12" x 4¾" x 7¾"
- · Weight without Dies: 40 lbs.

CAT. NO.	DESCRIPTION	PKG. QTY.
21940	40-Ton Hydraulic Head with Steel Case	1

www.tnb.com

**United States** 

Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 **Technical Services** 

Tel: 888.862.3289

