

Technical Specifications



CI0 / CI5



CI1-C



CI10 / CI11



CI1544




CI1544P



CIS-1X2



CIS-1 / CIS-4



CI66




CI66-FPP



CI66-T



CI66-PPH



CI66-SS



CI66-XL-2



CI66-XL

Cat. No.	Dimensions		Hole Size	Suggested Application NMD90 (loomex)
	H	W		
Cable Straps (Aluminum)				
CI0	0.44	0.63	3/16	14/3-12/3
CI1	0.50	0.56	3/16	10/3
CI1-C	0.50	0.50	3/16	14/2-12/2; 14/3-12/3
CI2	0.50	0.63	3/16	14/3-10/3
CI3	0.57	0.68	3/16	14/3-10/3
CI4	0.81	1.06	3/16	4/3
CI5	1.06	1.25	7/32	3/3-2/3
CI10	0.19	0.44	3/16	14/2
CI11	0.31	0.56	3/16	12/2-10/2
Nailing Straps (Zinc Plated Steel)				
CI1544	0.25	0.51	-	14/2-12/2
Nailing Straps (Polyethylene)				
CI1544-P	0.25	0.49	-	14/2-12/2
CI1546-P	0.25	0.75	-	14/2-8/2
Cable Staples (Galvanized Steel)				
CIS-1	0.25	0.48	-	14/2-12/2
CIS-2	0.44	0.54	-	2 cables 14/2 14/2-12/2-10/2-14/3-12/3
CIS-3	0.49	0.70	-	10/2-8/2; 14/3-10/3
CIS-4	0.76	0.86	-	8/3-6/3
Double Cable Staples (Galvanized Steel)				
CIS-1X2	0.25	0.48 x 2	-	14/2-12/2
CIS-1X2-FP3	0.25	0.48 x 2	-	14/2-12/2
CIS-1X2-FP5	0.25	0.48 x 2	-	14/2-12/2

Also suitable for NMWU90 of equivalent diameters.

Cat. No.	Suggested Application
Protector Plates (Galvanized Steel)	
CI66	For wood stud
CI66-FPP	For wood stud
CI66-PPH	For wood stud
CI66-SS	For metal stud
CI66-T	For wood stud
CI66-XL	For wood stud
CI66-XL-2	For wood stud

As required by C.E.C. rules 12-516 and 12-616.

