



## Fittings and Brackets

### Flat Fittings


**AB206**  
 AB206HDGC  
 AB206EG  
 AB206  
 AB206SS6C  
 Wt./C 35 lb.




**AB207**  
 AB207HDGC  
 AB207EG  
 AB207  
 AB207SS6C  
 Wt./C 52 lb.




**X207**  
 X207HDG  
 X207EG  
 X207  
 X207SS6  
 Wt./C 78 lb.




**X208**  
 X208HDG  
 X208EG  
 X208  
 X208SS6C  
 Wt./C 88 lb.




**AB219**  
 AB219HDGC  
 AB219EG  
 AB219  
 AB219SS6C  
 Wt./C 53 lb.



**AB220**  
 AB220HDGC  
 AB220EG  
 AB220  
 AB220SS6C  
 Wt./C 78 lb.




**AB240**  
 AB240HDG  
 AB240EG  
 AB240  
 Wt./C 69 lb.




**AB241**

Cat. No.	Bolt Size (in.)	Wt./C lb.
AB241-1/4*	1/4	18
AB241-5/16*	5/16	18
AB241-3/8*	3/8	18
AB241-1/2*	1/2	17
AB241-5/8*	5/8	15
AB241-3/4*	3/4	14




\*Finishes  
 • HDGC • GoldGalv®  
 • EG • SS6C

**AB242**  
 AB242HDGC  
 AB242EG  
 AB242  
 Wt./C 9 lb.




For use with either 3/8 in. or 1/2 in. hanger rod.


**AB253**  
 AB253HDGC  
 AB253EG  
 AB253  
 AB253SS6C  
 Wt./C 97 lb.




**AB255**  
 AB255HDGC  
 AB255EG  
 AB255  
 Wt./C 70 lb.




**AB257**  
 AB257HDGC  
 AB257EG  
 AB257  
 Wt./C 105 lb.




**AB261**  
 AB261HDGC  
 AB261EG  
 AB261  
 Wt./C 148 lb.



**AB263**  
 AB263HDGC  
 AB263EG  
 AB263  
 AB263SS6  
 Wt./C 150 lb.



**AB265**  
 AB265HDGC  
 AB265EG  
 AB265  
 Wt./C 105 lb.



Standard Dimensions	Value
Hole Spacing	→ 13/16 in. From End
Hole Spacing	→ 1-7/8 in. Centers
Hole Size	→ 9/16 in. Diam.
Material	→ 1-5/8 in. Width
Material	→ 1/4 in. Thick

Materials	Value
HDG(C)	→ Hot-Dipped Galvanized
EG(C)	→ ElectroGalvanized
(No suffix)	→ GoldGalv®
SS6(C)	→ Stainless Steel 316