


## Fittings and Brackets

### 90° Fittings


**AB284R**  
**AB284RHDG**  
**AB284REG**  
**AB284L**

Wt./C 230 lb.




**AB284L**  
**AB284LHDG**  
**AB284LEG**  
**AB284L**

Wt./C 230 lb.




**AB299**  
**AB299HDG**  
**AB299EG**  
**AB299**

Wt./C 40 lb.




**X201**  
**X201HDG**  
**X201EG**  
**X201**

Wt./C 65 lb.




**X204**  
**X204HDG**  
**X204EG**  
**X204**

Wt./C 1-90 lb.



**X289**  
**X289HDG**  
**X289EG**  
**X289**

Wt./C 105 lb.




**X299**  
**X299HDG**  
**X299EG**  
**X299**

Wt./C 38 lb.




**N205**  
**N205HDG**  
**N205EG**  
**N205**  
**N205SS6C**

Wt./C 74 lb.



**N219**  
**N219HDG**  
**N219EG**  
**N219**  
**N219SS6**

Wt./C 71 lb.



<b>Standard Dimensions</b>	Hole Spacing → 13/16 in. From End
	Hole Spacing → 1-7/8 in. Centers
	Hole Size → 9/16 in. Diam.
	Material → 1-5/8 in. Width
	Material → 1/4 in. Thick

<b>Materials</b>	HDG(C) → Hot-Dipped Galvanized
	EG(C) → Electrogalvanized
	(No suffix) → GoldGalv®
	SS6(C) → Stainless Steel 316