

Power-Assisted Compression Tools



Creates Hex-style crimp

TBM15I 15-Ton Hydraulic Crimping Head

- Head made of forged steel and insulated with rubber boot
- Longer, slimmer design enables easier access into tight spaces, such as in cable tray and central office applications
- Wider jaw opening eases crimping of larger lugs, C-Taps and H-Taps
- Uses 15600 Series dies; can also use 15500 Series dies with 15500-TB adaptor (refer to pp. E29–E44)

Cat. No.	Description	Pkg. Qty.
TBM15I	Insulated 15-Ton Hydraulic Head with Steel Case	1

15600 Series – Fits directly into tool for larger size connectors, 800 kcmil–1,500 kcmil.
 15500 Series – Used in conjunction with 15500-TB Adaptor, #8 AWG–750 kcmil

Specifications

- Installing Range:
 Up to 1500 kcmil copper lugs & splices
 Up to 1000 kcmil aluminum lugs & splices
 CHT814-10 to CHT750-350-1F copper H-Taps
 63105 to 63180 aluminum H-Taps
 54755 to 54790 C-Taps
- Output Force: 15-Ton
- Operating Pressure: 10,000 psi nominal
- Dimensions (L x W x H): 15-3/4 in. x 2-5/8 in. x 4-3/8 in.
- Weight: 16.5 lb.



Creates Hex-style crimp

21940 40-Ton Hydraulic Crimping Head

- Compact design delivers maximum pressure for larger lugs and splices
- Ideal for applications requiring larger lugs up to 2000 kcmil
- Uses 11300 and 11400 Series dies (refer to pp. E29–E44)

Cat. No.	Description	Pkg. Qty.
21940	Presse hydraulique de 40 tonnes avec mallette de transport en acier	1

Suggested replacement oil T&B Cat. No. 21061 or any light weight hydraulic fluid or automatic transmission fluid is recommended. Do not use silicon based fluids.

Specifications

- Installing Range:
 Up to 2000 kcmil copper lugs & splices
 Up to 2000 kcmil aluminum lugs & splices
- Output Force: 40-Ton
- Operating Pressure: 10,000 psi nominal
- Dimensions (L x W x H): 12 in. x 4-3/4 in. x 7-3/8 in.
- Weight: 40 lb.