

## Channels and Concrete Inserts

### Channel Selection Chart

| CHANNEL | HOLE CONFIGURATIONS |   |    |   |    | LENGTH   | FINISH ON STEEL |      |       |       |           |        | SPECIAL MATERIALS |       |       |        |
|---------|---------------------|---|----|---|----|----------|-----------------|------|-------|-------|-----------|--------|-------------------|-------|-------|--------|
|         | HS                  | S | SW | P | KO |          | ft.             | B(C) | PG(C) | EG(C) | GoldGalv® | HDG(C) | GR(C),GY(C),WH(C) | AL(C) | T316L | SS6(C) |
| A1200   |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| A1400   |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| AR1600  |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| B1200   |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| B1400   |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| BR1600  |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| C1200   |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| D1200   |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| E1200   |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |
| H1200   |                     |   |    |   |    | 10 or 20 |                 |      |       |       |           |        |                   |       |       |        |

### Legend

| EXAMPLES   | HOLE CONFIGURATION |                   | FINISH ON STEEL |   | SPECIAL MATERIALS |                           |
|--|--------------------|-------------------|-----------------|---|-------------------|---------------------------|
|  | Suffix             |                   | Suffix          |   | Suffix            |                           |
| <b>A120010PG</b><br>Plain channel,<br>10 ft., pre-<br>galvanized finish      | <b>blank</b>       | Plain, no holes   | <b>BC</b>       | Bare  | <b>AL</b>         | Aluminum                  |
|  | <b>HS</b>          | Half slot         | <b>PGC</b>      | Pre-galvanized                                      | <b>SS6 (C)</b>    | Stainless Steel Type 316  |
| <b>B1400P10</b><br>Punched channel,<br>10 ft.,<br>GoldGalv® finish           | <b>S</b>           | Slotted           | <b>EGC</b>      | Electrogalvanized                                   | <b>T316L</b>      | Stainless Steel Type 316L |
|  | <b>SW</b>          | Slotted wide      | <b>Blank</b>    | GoldGalv®   |                   |                           |
|  | <b>P</b>           | Punched           | <b>HDGC</b>     | Hot dipped galvanized                               |                   |                           |
| <b>E1200HS20HDG</b><br>Half slot channel,<br>20 ft. hot dipped<br>galvanized | <b>KO</b>          | Knockout          | <b>GR,GY,WH</b> | Epoxy paint in green (GR), grey (GY), or white (WH) |                   |                           |
|  |                    | Standard offering |                 | A minimum order quantity may apply                  |                   |                           |

### Hole Configuration

