

# Metallic — aluminum

## Covers — accessories for covers


A

### Quantity of standard cover clamps required

Straight section 1.8m (6 ft.)	4 pcs.	Tees	6 pcs.
Straight section 3m (10 ft.) and 3.7m (12 ft.)	6 pcs.	Crosses	8 pcs.
Horizontal and vertical bends	4 pcs.		

IMPORTANT NOTE: "B" in Cat. No. indicates this accessory can be used for both styles.

**Note: When using heavy-duty cover clamp, only half the quantity of pieces are required.**




### Economical cover clamp

Rigid indoor cover clamp for flat and flanged covers.

Cat. No.	Material	Side rail height (in.)
ABW-SCC	Zinc-plated steel	All sizes

Cannot be used with U-style fittings.



### Universal fitting cover clamp

Rigid indoor cover clamp for flat and flanged covers.

Cat. No.	Material	Side rail height (in.)
ABW(*)FCC	Zinc-plated steel	4
		5
		6
		7

(\*) Insert side rail height



### Heavy-duty cover clamp

Wraparound design offers added protection for rugged applications and outdoor conditions. Hardware included.

Cat. No.	Material	Side rail height (in.)	Tray width (in.)
ABW4(*)HCC	Aluminum	4	6
ABW5(*)HCC		5	9
ABW6(*)HCC		6	12
ABW7(*)HCC		7	18

(\*) Insert tray width

24
30
36
42

T&B aluminum cable tray is composed of two distinct systems, H-style and U-style. These systems are interchangeable.