

EMT

Compression Fittings and Couplings

- Models from 2-1/2 to 4 in. are also suitable for rigid and IMC conduit



TC111A



TC711A



Cat. No.		Trade Size (in.)
Regular	Insulated	
EMT Compression Fittings (Zinc-plated steel)		
TC111A	TC711A	1/2
TC112A	TC712A	3/4
TC113A	TC713A	1
TC114A*	TC714A	1-1/4
TC115A*	TC715A	1-1/2
TC116A*	TC716A	2
TC117A	TC717A	2-1/2
TC118A	TC718A	3
TC119A	TC719A	3-1/2
TC1110A	TC7110A	4

UL FILE NO. E-16592. * O-rings are supplied.
Concrete-tight.



TK111A



Cat. No.	Trade Size (in.)
EMT Compression Couplings (Zinc-plated steel)	
TK111A	1/2
TK112A	3/4
TK113A	1
TK114A	1-1/4
TK115A	1-1/2
TK116A	2
TK117A	2-1/2
TK118A	3
TK119A	3-1/2
TK1110A	4

UL FILE NO. E-16592.
Concrete-tight.

CI5804 (-IT) / CI5832 (-IT)



Zinc Die Cast Locknut
IT: with insulated throat



Cat. No.		Trade Size (in.)
Regular	Insulated	
EMT Compression Fittings (Zinc Alloy)		
CI5804	CI5804-IT	1/2
CI5806	CI5806-IT	3/4
CI5808	CI5808-IT	1
CI5810	CI5810-IT	1-1/4
CI5812	CI5812-IT	1-1/2
CI5816	CI5816-IT	2
CI5820	CI5820-IT	2-1/2
CI5824	CI5824-IT	3
CI5832	CI5832-IT	4

Concrete-tight.

CI5904 / CI5932



Cat. No.	Trade Size (in.)
EMT Compression Couplings (Zinc Alloy)	
CI5904	1/2
CI5906	3/4
CI5908	1
CI5910	1-1/4
CI5912	1-1/2
CI5916	2
CI5920	2-1/2
CI5924	3
CI5932	4

Concrete-tight.