
Device Boxes

Armoured and Nonmetallic Sheathed Cable Clamps









BC1004-L

Flush ears.

BC1004-LH

Positioning tabs. Provision for external nailing. Two embossed mounting slots for internal screw installation.

CI1004-LB

Side bracket wood stud.

BC1018-LHTQ

One screw mounting provisions for external nailing.





Provision for external nailing.



CI3004-LSSX-1

1 in. recessed brackets for 2-1/2 in. and 3-5/8 in. steel studs. Brackets positioned for 2 layers of 1/2 in. drywall.



Cat. No.	Volume (Cu. in.)	Features		Pryouts
		Ears	Bracket	ends
3 in. Deep — Gangable — 3 in. x 2 in.				
BC1004-L	15.0	flush	-	4
BC1004-LH	15.0	-	P. Tabs	4
CI1004-LB	16.0	-	"B"	4
BC1018-LHTQ	18.0	-	P. Tabs	4
BC3004-LH	18.0	-	-	4
Cl3004-LSSX	18.0	-	"SSX"	4
Cl3004-LSSX-1	18.0	-	"SSX"	4
Cl3004-LSSAX-1.25*	18.0	-	"SSX"	4

^{*} Brackets positioned for 2 layers of 5/8 in. drywall

