

Device Boxes

Armoured and Nonmetallic Sheathed Cable Clamps





CI2104-LLEA

Holding prongs and prepositioned depth tabs.

CI2104-LSSAX

"Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs. With integral support bracket.



CI2104-LSSA-2X

2 gang. "Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs. With integral support bracket. 3 gang. "Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs. With integral support bracket.



CI2104-LSSA-3X



| Cat. No. | Width (in.) | Volume (Cu. in.) | Features | | Pryouts |
|--|----------------|---------------------|----------|---------|---------|
| | | | Ears | Bracket | ends |
| 2-1/2 in. Deep — Non-Gangable — 3 in. High | | | | | |
| CI2104-LLEA | 2 | 12.5 | - | P. Tabs | 4 |
| CI2104-LSSAX | 2 | 12.5 | - | P. Tabs | 4 |
| CI2104-LSSA-2X | 3-3/4 | 25 | - | "SSX" | 8 |
| CI2104-LSSA-3X | 5-1/2 | 37.5 | - | "SSX" | 12 |
| CI2104-LSSA-4X | 7-3/8 | 50.0 | - | "SSX" | 16 |