. . . .



Vapour Barriers

Features

- Made from tough, resistant material which can be used without cracking at extreme cold temperatures
- Transparent material makes installation easy and safe
- Flange is constructed to ensure a good seal on panel surface



| CI1004-VB | CI5254-VB | CI72171-VB | CIDS-55 |
|-----------|-----------|------------|---------|
| | | | |

| Cat. No. | Description | | | |
|------------------------------|---|--|--|--|
| Vapour Barriers — Soft Shell | | | | |
| BCVB-1* | For 2 in. x 3 in. single device boxes up to 3 in. deep | | | |
| BCVB-2* | For 4 in. square and 2 gang 2 in. x 3 in. device boxes up to 3 in. deep | | | |
| BCVB-3* | -3* For 3 gang 2 in. x 3 in. device boxes up to 3 in. deep | | | |
| CIVB-4* | For 4 gang 2 in. x 3 in. device boxes up to 3 in. deep | | | |
| BCVB-54* | For octagonal boxes up to 2-1/8 in. deep | | | |
| Vapour Barriers — Hard Shell | | | | |
| CI1004-VB* | For 2 in. x 3 in. single device boxes up to 3 in. deep | | | |
| CI5254-VB* | For 4 in. square and 2 gang 2 in. x 3 in. boxes up to 3 in. deep | | | |
| CI72171-VB* | For 4-11/16 in. square boxes up to 2-1/8 in. deep | | | |
| Door Switches | | | | |
| CIDS-55 | 3-11/16 in. H x 1-11/32 in. W x 1-1/2 in. deep 4.5 cu. in. | | | |
| | Light's on when door's opened | | | |
| | Kit contains: • 3 A, 125 V A.C. switch with steel push button • Steel box and mounting plate • Mounting screws and wire connectors • Instruction sheet | | | |

* CSA not applicable



