

# Accessories

## Tube clamps



GL

### GL

#### Tube clamp, one-piece

- Used in general machine and installation applications

Order No. black	Order No. grey	Fits to conduit size		Width	Fixing screw
		NW	metric		
BGL-07	SGL-07	07	10	25.0 mm	1 x M4
BGL-10	SGL-10	10	12	27.0 mm	1 x M4
BGL-12	SGL-12	12	16	31.0 mm	1 x M4
BGL-17	SGL-17	17	20	39.5 mm	1 x M5
BGL-23	SGL-23	23	25	49.0 mm	1 x M5
BGL-29	SGL-29	29	32	57.0 mm	1 x M6

- Integrated rib provides axial strain relief
- Allows turning of the conduit, thus avoiding torsion stresses
- Pre-fixation on the conduit possible

6



GH

### GH

#### Tube clamp, one-piece

- Used in general machine and installation applications

Order No. black	Order No. grey	Fits to conduit size		Width	Fixing screws
		NW	metric		
BGH-23	SGH-23	23	25	16.0 mm	2 x M5
BGH-29	SGH-29	29	32	19.0 mm	2 x M6
BGH-36	SGH-36	36	40	24.0 mm	2 x M6
BGH-48	SGH-48	48	50	24.0 mm	2 x M6
BGH-56	SGH-56	56	68	26.0 mm	2 x M8
BGH-70	SGH-70	70	80	30.0 mm	2 x M8
BGH-95	SGH-95	95	106	30.0 mm	2 x M8

- Integrated rib provides axial strain relief
- Allows turning of the conduit, thus avoiding torsion stresses
- Pre-fixation on the conduit possible
- Allows solid fixation with 2 screws



SGB

### SGB

#### Tube clamp

- For fixation of static conduits

Order No.	Fits to conduit size		Width	Fixing screw
	NW	metric		
SGB-07	07	10	13.0 mm	1 x M4
SGB-09	10	12	13.0 mm	1 x M4
SGB-11	12	16	13.0 mm	1 x M4
SGB-16	17	20	16.0 mm	1 x M5
SGB-21	23	25	16.0 mm	1 x M5
SGB-29	29	32	19.0 mm	1 x M6
SGB-36	36	40	19.0 mm	1 x M6
SGB-48	48	50	19.0 mm	1 x M6

- Galvanized steel
- Elastomer profile (EPDM) free from halogens
- Smooth connection to PMA conduits
- Good resistance to ozone and ageing
- Temperature range: –40 °C to +120 °C