

Automation Products

Automation accessories



SH

SH

Tube clamp, one-piece

- To be used with GN half-shells to optimally fix/guide conduits
- Serves as a fixation for functional inserts (TK, KE) which increase the degrees of freedom for cable packs and reduce mechanical stresses

Order No. black	Fits with half-shell GN			Fits to conduit size		Length	Height	Width
	Fine Profile	Coarse Profile	Slide	NW	metric			
BSH-R29	BGN-S29T	BGN-S29G	BGN-R29	29	32	71.0 mm	67.0 mm	26.0 mm
BSH-R36	BGN-S36T	BGN-S36G	BGN-R36	36	40	81.5 mm	77.5 mm	26.0 mm
BSH-R48	BGN-S48T	BGN-S48G	BGN-R48	48	50	96.0 mm	91.0 mm	26.0 mm
BSH-R56	-	BGN-S56G	BGN-R56	56	68	112.5 mm	103.5 mm	30.0 mm
BSH-R70	-	BGN-R70G	BGN-R70	70	80	149.0 mm	144.0 mm	40.0 mm

- Content of delivery:
Tube clamp, 1 PT screw, 1 straight pin



GN

GN

Strain relief half-shell

- For conduit fixation in combination with tube clamp SH
- Fixes conduit against axial movements
- Allows for rotation of the conduit (within tube clamp SH)

Order No. black	Fine Profile	Coarse Profile	Fits with:	Fits to conduit size		Outside	Width
				NW	metric	∅	
BGN-S29T	BGN-S29G	BGN-S29G	BSH-R29	29	32	47.0 mm	34.0 mm
BGN-S36T	BGN-S36G	BGN-S36G	BSH-R36	36	40	55.0 mm	34.0 mm
BGN-S48T	BGN-S48G	BGN-S48G	BSH-R48	48	50	66.5 mm	36.5 mm
-	BGN-S56G	BGN-S56G	BSH-R56	56	68	81.0 mm	38.0 mm
-	BGN-R70G	BGN-R70G	BSH-R70	70	80	105.0 mm	45.0 mm
-	BGN-S70G	BGN-S70G	BLH-R70G	70	80	93.5 mm	38.0 mm



GN

GN

Slide half-shell

- Insert in combination with tube clamp SH
- Allows gliding of the conduit in the clamps and thus reduce axial stress on the conduit
- Allow for both rotation of the conduit and axial movement

Order No. black	Fits with:	Fits to conduit size		Outside	Width
		NW	metric	∅	
BGN-R29	BSH-R29	29	32	47.0 mm	34.0 mm
BGN-R36	BSH-R36	36	40	55.0 mm	36.0 mm
BGN-R48	BSH-R48	48	50	66.5 mm	36.5 mm
BGN-R56	BSH-R56	56	68	81.0 mm	38.0 mm
BGN-R70	BSH-R70	70	80	105.0 mm	45.0 mm