

## Accessories and Tools

### AFN2 Universal Safety Clips

- Pre-installed in the IP66 and IP68GT range of connectors
- Allow for a quick and easy connection to PMAFLEX® conduits by just pushing the conduit into the connector
- High-grade formulated polyamide
- Self extinguishing
- Free from halogens and cadmium
- Fits fine (T) and coarse (G) conduit profiles



**Temperature range:** -40° C to 105° C;  
Short term 160° C

Cat. No.	Fits to NW	Fits to Profile	Dimensions Width (mm)	Dimensions Length (mm)	Dimensions Thickness (mm)	
IP66, Dark Grey	7	G + T	14.0	14.0	7.0	
AFN2-07GT	7		17.5	17.0	8.0	
AFN2-10GT	10		20.5	20.0	7.3	
AFN2-12GT	12		26.5	22.0	8.0	
AFN2-17GT	17		34.0	27.5	11.8	
AFN2-23GT	23		40.5	32.0	11.8	
AFN2-29GT	29		49.5	38.8	9.5	
AFN2-36GT	36		62.0	47.0	9.5	
AFN2-48GT	48					

### OVN2 Oval Clips

- Secure the conduit within the PMAFIX® connectors and distributors
- Connections made with a high degree of safety
- High-grade formulated polyamide
- Easy to install
- Self extinguishing
- Free from halogens and cadmium
- Fits fine (T) and coarse (G) conduit profiles



**Temperature range:** -40° C to 105° C;  
Short term 160° C

Cat. No.	Fits to NW	Fits to Profile	Dimensions Width (mm)	Dimensions Length (mm)	Dimensions Thickness (mm)	
IP68, Dark Grey	7	G + T	14.0	14.0	6.0	
OVN2-07	7		17.5	17.0	7.0	
OVN2-10	10		21.0	19.0	6.0	
OVN2-12	12		26.5	22.5	7.0	
OVN2-17	17		34.0	27.5	10.5	
OVN2-23	23		40.5	32.0	10.5	
OVN2-29	29		49.5	39.0	8.5	
OVN2-36	36		62.0	47.0	8.5	
OVN2-48	48					

### WPS Water-Impact Protection

- Increased protection of PMAFIX® fittings against water jet impact
- Meet increased ingress protection requirements regarding high-pressure/ steam jet cleaning
- High-grade, specially formulated polyamide 6, extremely shock resistant
- Self extinguishing
- Free from halogens and cadmium
- Based on PMAFIX®/PMAFLEX® system with ingress protection of IP68
- Additional protection against water jet impact; increased protection up to IP69K
- Two-piece water-impact protection with click cap
- Fits all PMAFLEX® conduit profiles



**Temperature range:** -45° C to 105° C;  
Short term 160° C

Cat. No.	Fits to NW	Fits to Profile	Outside Diameter (mm)	Dimensions Thickness (mm)
IP69K, Black	10	G + T	22.0	8.0
WPS-NW10	10		26.0	8.0
WPS-NW12	12		33.0	8.0
WPS-NW17	17		40.0	9.0
WPS-NW23	23		47.0	9.5
WPS-NW29	29		59.0	10.0
WPS-NW36	36		71.0	10.0
WPS-NW48	48			