
700 SERIES RACEWAY WIRE FILL CAPACITIES FOR COMMUNICATIONS						
	CABLE/WIRE SIZE	O.D. (Appr Inches	ox. Dia.) [mm]	40% FILL		
UNSHIELDED TWISTED PAIR	4-pair, 24 AWG, Cat 3 4-pair, 24 AWG, Cat 5e 4-pair, 24 AWG, Cat 6 4-pair, 24 AWG, Cat 6a* 25-pair, 24 AWG	0.190 0.210 0.250 0.354 0.410	[4.8] [5.3] [6.3] [9.0] [10.4]	3 3 2 1 0		
COAXIAL	RG6/U	0.270	[6.9]	1		
FIBER	ZipCord Round 4 Strand Fiber Round 6 Strand Fiber	0.118 x 0.236 0.187 0.256	[3 x 6] [4.8] [6.5]	3 3 2		

700 SERIES RACEWAY WIRE FILL CAPACITIES FOR POWER					
WIRE SIZE THHN/THWN	0 Inches	.D. [mm]	NO. OF CONDUCTORS 40% FILL		
14 AWG	0.111	[2.8]	10		
12 AWG	0.130	[3.3]	7		
10 AWG	0.164	[4.2]	4		

NOTE: For additional information, refer to the Technical Section.

* Category 6 augmented (6a) cable for 10 gigabit ethernet – max allowed cable diameter per addenda No. 11 ANSI TIA/EIA 568-B.2.



NOTE: Use #8 flathead screws with all fittings requiring screws except V704. With V704, use #8 panhead screws.

