COMMUNICATIONS CONNECTIVITY

CM SERIES™ COMMUNICATION MODULES




Wiremold® CM Series™ Communication Modules provide a variety of unloaded modules to accept devices from other manufacturers. These open system modules provide a flexible and aesthetically pleasing way to connect communication cabling at the point-of-use.

CODE REFERENCE

cULus Listed Communication Circuit Accessories: File E145222 Guide DUXR. Meets Article 800 of NEC. Meets Article 60-308 of CEC.


CM Series Communication Modules Ordering Information

CM2-U1KEYA 2A Single Flushmount Unloaded Keystone Module




Accepts keystone jacks with a latching area of 0.58" x 0.76" [14.7mm x 19.3 mm]. Also available in white (CM2-U1KEYA-WH), light grey (CM2-U1KEYA-GY), black (CM2-U1KEYA-BK) and grey (CM2-U1KEYA-G).

CM2-U1ATT 2A Single Systimax (Avaya) Unloaded Module



Accepts both M-series jacks and LC fiber adapters. Also available in white (CM2-U1ATT-WH), light grey (CM2-U1ATT-GY), black (CM2-U1ATT-BK) and grey (CM2-U1ATT-G).

CM2-U2KEYA 2A Dual Flushmount Unloaded Keystone Module



Accepts keystone jacks with a latching area of 0.58" x 0.76" [14.7mm x 19.3 mm]. Also available in white (CM2-U2KEYA-WH), light grey (CM2-U2KEYA-GY), black (CM2-U2KEYA-BK) and grey (CM2-U2KEYA-G).

CM2-U2ATT 2A Single Systimax (Avaya) Unloaded Module



Accepts both M-series jacks and LC fiber adapters. Also available in white (CM2-U2ATT-WH), light grey (CM2-U2ATT-GY), black (CM2-U2ATT-BK) and grey (CM2-U2ATT-G).

COLOR OPTIONS













CM Series" Communication Modules standard color is ivory. For other colors, add one of the following suffixes: "-WH" for white, "-GY" for light gray (matches aluminum and nonmetallic products), "-BK" for black, or "-G" for gray (matches Wiremold gray steel products).



CM SERIES™ COMMUNICATION MODULES

Ordering Information

CM Series Communication Modules Speciaty Mounting Adapters Ordering Information

CM-EPLA End Plate



End plates with two outlet ID labels with clear covers and two matching screw covers. Required when mounting modules into 4050, 5450, 5550, and WSA07-4A device mounting brackets, and the V2444D-2A and 2344SD-2A 2-gang divided raceway box. Also available in white (CM-EPLA-WH), fog white (CM-EPLA-FW), and grey (CM-EPLA-G).

AB2TJ Ortronics® TracJack 2A Mini Mounting Adapter



Accepts two Ortronics® TracJack Inserts. Also available in white (AB2TJ-WH), light grey (AB2TJ-GY), black (AB2TJ-BK) and grey (AB2TJ-G).

CM-2AB CM2/Activate 2A Mini Mounting Adapter




Accepts one CM2 Series communication module or one Pass & Seymour 2A Activate Series insert. Also available in white (CM-2AB-WH), light grey (CM-2AB-GY), black (CM-2AB-BK) and grey (CM-2AB-G).

ABS2 Ortronics® Series II 2A Mini Mounting Adapter



Accepts one Ortronics® Series II 1-unit insert. Also available in white (CABS2-WH), light grey (ABS2-GY), black (ABS2-BK) and grey (ABS2-G).

CM-MAB 6A Mini Mounting Adapter



6A opening. Must be purchased separately for mounting communication modules in service fittings where it is indicated they are not included. Also available in light grey (CM-MAB-GY), black (CM-MAB-BK) and fog white (CM-MAB-FW).

MAB3S2 Ortronics® Series II 6A Mounting Adapter



Accepts three Ortronics® Series II 1-unit inserts. Also available in light grey (MAB3S2-GY), black (MAB3S2-BK) and grey (MAB3S2-G).

MAB6TJ Ortronics® TracJack 6A Mounting Adapter



Accepts six Ortronics® TracJack inserts. Also available in white (MAB6TJ-WH), light grey (MAB6TJ-GY), black (MAB6TJ-BK) and grey (MAB6TJ-G).

CM-ARA Angled Raceway Adapter



For use with multi-channel raceway device brackets and WallSource device mounting brackets. Angled exit provides additional mounting depth required for audio/visual connections as well as ensuring the required bend radius for UTP and fiber optic cabling. Holds two CM2 Series modules or two 2A inserts. Fits 5507 Series Faceplate opening. Also available in white [CM-ARA-WH], light grey (CM-ARA-GY), black (CM-ARA-BK) and grey [CM-ARA-G].