
EVOLUTION[™] 6AT SERIES POKE-THRU DEVICES

Evolution 6AT Series Poke-Thru Devices Ordering Information (continued)

6STCPAV Recessed Prewired Audio/Video **Assembly with Disposable Plate**



NOTE: UL Fire Classified for up to 2 hour rated floors. NOTE: Receptacles can be wired as a standard or isolated ground device.

Includes 6" diameter poke-thru stem assembly with a disposable plate. Devices are recessed 3 1/4" [83mm] below floor surface. No cover assembly is included. For use with the following cover assemblies (purchased separately): 6CTC and 6CT Series.

INCLUDED

For Side Compartments:

- One (1) Proprietary 20AMP Duplex Power Receptacle installed
- One (1) 682A Device Plate
- One (1) 68MAAP Device Plate

For Center Compartment:

- One (1) 6DEC Mounting Plate
- One (1) 6AAP Mounting Plate
- One (1) 6MAAP Device Plate

For Bottom Feed Compartments:


- One (1) 5PTHA 1/2-Gang Pass-Through Housing Assembly
- One (1) 1PTHA 1-Gang Pass-Through Housing Assembly
- One (1) 575CHA 1/2-gang 3/4" Conduit Housing Assembly**
- * Tunneling extends from the 5BLH to 575CHA so that power cables from the 20A duplex receptacle mounted on the left side of the poke-thru device are run into the junction box attached to the 575CHA.
- ** Also includes junction box attached to the 3/4" conduit.

ABPLUG6 Abandonment Plug Assembly



Complete abandonment plug assembly for 6" opening. Assembly includes intumescent fire stop material to maintain a 2 hour fire rating of the floor

6STCP **Recessed Prewired Assembly with Disposable Plate**



Includes 6" diameter poke-thru stem assembly with a disposable plate. Devices are recessed 3 1/4" [83mm] below floor surface. No cover assembly is included. For use with the following cover assemblies (purchased separately): 6CTC and 6CT Series.

INCLUDED

• Two (2) Proprietary 20AMP Duplex Power Receptacles installed


For Center Compartment:

- One (1) 6ACT8A Mounting Plate
- One (1) 6TRAC Mounting Plate
- One (1) 6SER Mounting Plate

For Bottom Feed Compartment:

- One (1) 5BLH 1/2-Gang Blank Housing*
- One (1) 1PTHA 1-Gang Pass-Through Housing Assembly
- One (1) 575CHA 1/2-Gang 3/4" Conduit Housing Assembly**
- NOTE: For more information on Device Plates and Bottom Feed Plates and on the additional options available, see the Device Plates and Bottom Feed Plates sections found later in this document.


6PPS 6" Pre-Pour Poke-Thru Sleeve



Nonmetallic sleeve attaches to structural decking and plywood decking designs while maintaining a 6"-6 1/8" diameter cast in hole. Unit includes three (3) attachment legs, two (2) end caps and three (3) thumb screws.

Evolution 6AT Series Cover Assemblies Ordering Information


6CTC^{*} Surface Style Cover Assembly



Die-cast aluminum cover assembly. Cover assembly is available in the following powder coated finishes: black (6CTCBK), gray (6CTCGY), nickel (6CTCNK), brass (6CTCBS), and bronze (6CTCBZ). 6CTC Series

cover assemblies designed for use with 6STCP. 6STC. and 6STCPAV Poke-Thru Stem Assemblies.

6CT^{*} Flush Style Cover Assembly



Die-cast aluminum cover assembly. Cover assembly is available in the following powder coated finishes: black (6CTBK), gray (6CTGY), nickel (6CTNK), brass (6CTBS), and bronze (6CTBZ). 6CT Series cover assemblies

designed for use with 6STCP, 6STC, and 6STCPAV Poke-Thru Stem Assemblies. Includes one (1) 6TS Tile Shim.

* Add suffix "TR" to the end of the part number to indicate tamper-resistant cover assembly. Tamper-resistant versions are secured with a single tamper-resistant screw.

POKE-THRU DEVICES

For Side Compartments: NOTE: UL Fire Classified

for up to 2 hour rated floors.

device.

- NOTE: Receptacles can be wired as a standard or isolated ground