


POWER COMMANDER® IQ SERIES

Ordering Information

Power Commander IQ Series Ordering Information (continued)

SPDU8-1U



Eight (8) 15A simplex outlets. Black housing.

Length: 19" [1.5m]
 Width: 1 5/8" [41mm]
 Depth: 6 1/4" [159mm]

AC Voltage Input	100 to 125V
AC Voltage Output	100 to 125V
Frequency	60 Hz
Load Capacity	15A
Output Receptacle	8 switched NEMA 5-15
Product Warranty	2 years
Power Cable – AWG Length & Plug Type	14/3 SJT Type, 5-15P straight blade, 4 1/2 ft. [1.4m]
Console Interface Local Master Port	1 RS232 Port. RJ-45 Connector. Data: 7 or 8 bits. Stop Bits: 1 or 2. Parity: None, Odd or Even. Flow Control: None or RTS/CTS. Baud rate 2400 to 115200.
Temperature Sensing Port	Digital Input Port – RJ11
Network Interface	10-Base-T RJ45.
Display	8 Power Outlet On/Off status LEDs, 2 Network LEDs. 2 digit LED display [1.00" x 0.65"] [25mm x 16.5mm] for AC Current Draw Status.
Network Protocols	ICMP, TCP/IP, DHCP Telnet, DNS, POP3/SMTP, SNMP, HTTPS/HTTP, and BootP
Weight	7 lbs. Shipping Weight
Operational Temperature Environment	32F° – 122F° [0C° – 50C°]
Storage Temperature	-20F° – 140F° [-29C° – 60C°]
Humidity	10% – 90% RH